



N480 High-Value 4-Bay NAS Your Personal Cloud







SE ARRING

Thecus

- ()

1

*

U

Ó

Thecus NAS

↓ ESC



Experience ThecusOS[™] 7.0

Redesigned User Interface Optimized Storage Management Streamlined Application Use P2P Connectivity via Orbweb.me App

Enjoy Your Home Theater

Built-in HDMI Output/DisplayPort/SPDIF Seamless 4K Multimedia Playback Media Streaming via Apple TV/Chromecast Media Streaming to XBOX360/PS4

Reliable Data Protection

Bundled with Free Acronis & Antivirus Thecus System Failover Secure Remote Access with VPN Dropbox/Amazon S3/ElephantDrive







Snapshot





Local Display

Photo Center Download Manager iTunes Server

iSCSI N

NAS App Center

Mobile Access

Thecus Cloud

www.Thecus.com

N4810



Processor

Intel[®] Celeron[™]N3160 Quad-Core System Memory

4GB DDR3

LAN Interface • RJ-45x2: 10/100/1000 BASE-TX Auto MDI/MDI-X

WOL supported

USB Interface

- USB 3.0 host port x3 (front x1, back x2) (A Type)
- USB 3.0 host port x1 (back x1) (C Type) LCM Module

LCM display

• 4 buttons (ENTER, ESC, UP, DOWN)

Software Functions

RAID

- RAID Modes: RAID 0, 1, 5, 6, 10 and JBOD
- · Auto-rebuild: Supported
- Hot-swap: Supported
- · Hot Spare: Supported
- RAID Expansion: Supported RAID Volume Encryption: AES256bit
- Disk

- Power Management: Available spin-down while idle setting
- Bad Block Scan: Supported
- SMART Info: Supported
- SMART Test: Supported
- · Disk Roaming: Supports volume-based roaming to other Thecus NAS (Require ThecusOS 7 64 bit)
- Disk Wipe and Clone: Supported
- Disk Security: Supported

Network

- · Configuration: Fixed IP address, dynamic IP address
- Transport Protocols: TCP/IP/Appletalk
- File Protocols: SMB/CIFS, HTTP/HTTPS, FTP, NFS v4, AFP · Link Aggregation: Load balance, Failover, 802.3ad,
- Balance-XOR, Balance-TLB, Balance-ALB, Broadcast TCP/IP: IPV6 & IPV4
- DDNS: Supported
- SSH: Supported
- UPnP: Supported
- UPnP Port forwarding: Supported
- Bonjour: Supported
- VPN Server: Supported

vLan: Supported

- System status
- System Monitor: Monitoring CPU, memory, network utilization and protocols access user count
- Syslog Management:
- 1. Send syslog to assigned location
- 2. Act as syslog server to receive log info from other systems

Data Áccess

- Client OS Support:
- Windows XP and after
- Windows Server 2003 and after
- UNIX/Linux
- Mac OS X
- FTP: Built-in FTP server with bandwidth control Secure FTP
- Built-in secure FTP server with bandwidth control
- Email: sales@thecus.com
- Official Website: www.thecus.com
- For Windows NAS: wss.thecus.com
- Reseller Center: www.thecus.com/reseller index.php
- NAS App Center: www.thecus.com/sp_app_center.php

- **HDMI Output** HDMI port (back x1) **DP Output**
- DP port (back x1)
- SPDIF
- SPDIF port (back x1)
- **Disk Interface**
- 4 x SATA for internal, support SATA II / SATA III hard disk Power Supply

Environment

Chassis

Certificates

Cloud Backup

File System

Administration

Utility Program:

DDNS: Supported

Thecus Wizord[™]

Data Security

Others

Capacity Expansion

other Thecus NAS

Recycled Bin: Supported

Thecus T-OnTheGo[™]

• RoHS

• WEEE

Temperature: 0°C to 40°C (Operation)

• Humidity: 0 ~ 80 % R.H. (Non-condensing)

• 192 x 172 x 250 (mm) / 7.56 x 6.77 x 9.84 (in)

-40°C to 70°C (Non-operation)

4bays Tower Metal Chassis

· CE/FCC/C-Tick/VCCI/BSMI

DropBox: Supported (via module)

Amazon S3: Supported

Type: Journaling File System

MS Windows Setup Wizard

Mac OS X Setup Wizard

the system administrator

Supports Windows XP and after

Mobile Applications (iOS/Android)

Offers fast NAS Setup via your phone

Antivirus: Supported (via module)

Scale-Out: Dynamic Volume Expansion

ISO Mount: Supported
Local Display: X-Window via HDMI output

Retail/Reseller Information

Upload, download and stream multimedia

multimedia and webcam via P2P connection

Thecus Connect[™] (Android):

SNMP Trap: System information trap out

P2P Connection: Mail or FB account to register

Provides live up-to-date information of your NAS

Orbweb.me: Uploading, downloading, streaming

Stackable: Can extend for 5 additional iSCSI volumes from

ElephantDrive: Supported (via module)

Language Support: Unicode Support

Folder Quota: Supported (Btrfs only)

Authorization (ACL): "Read," write," or "deny" privileges to

individual users or groups in folders and sub-folders • User Quota: Supported (exclude Btrfs)

User Interface:Web-based user interface supports

Japanese, French, German, Italian, Spanish, Russian.

Email Notifications: Sends system messages via email to

English, Traditional Chinese, Simplified Chinese,

Dimensions (HxWxD)

- 90W external power adapter
- **Power Management**
- Auto power on after shutdown due to power loss
- Buttons
- Power button
- TFTP:
- Users can download and upload files with TFTP programs Download Manager:
- BT download (via Transmission module)
- NZB download (via NZB module) WebDAV/WebDAV SSL: Supported
- Printer Server (IPP):
- 1. Supports USB printers
- 2. Supports a wide range of IPP printers
- 3. Client can manage print tasks (list/delete) via web

user interface Data Backup

- Client Incremental Data Backup:
- Acronis True Image (OEM version)
- Client System Disaster Recovery:
- Acronis True Image (OEM version) Mac OS X Time Machine: Supported
- Local folder/iSCSI Backup: Supported
- Remote folder/iSCSI Backup: Supported
- Snapshot: Supported (Btrfs)
- System Failover: Supported

Block Level Access

- iSCSI Target/Initiator: Supports Microsoft/Mac OS X/
- Linux initiators and Thecus NAS targets
- iSCSI Thin Provisioning: Supported
- MPIO: Supported
- MCS: Supported **Clustering: Supported**
- SCSI3 persistent group reservation: Supported
- **Power Management**

Scheduled Power On/Off: Supported

- Volume Management
- Multiple RAID: Supported Multiple File System Selectable: EXT4/XFS/Btrfs

Local User: Supports built-in user accounts

Local Group: Supports built-in user groups

Facebook: www.facebook.com/Thecus

Twitter: twitter.com/Thecus Storage

RSS: www.thecus.com/rss news.php

YouTube: www.youtube.com/thecusstorage

Forum: forum.thecus.com

Blog: blog.thecus.com

Multimedia Support

Windows ADS: Supported
 LDAP: Supported

 Photo Center: Supported File Center: Supported

 APP Center: Supported Surveillance Center: Supported

User Authentication

User Profile

f

E

Yes

Ŵ

Design and specifications are subject to change without prior notice. Copyright © 2017 Thecus Technology Corp. All rights reserved.

• iTunes Server: Supports AAC, MP3 w/ID3 tag and WAV · Media Server: Supports uPnP AV streaming protocol (via Module)